

UT80 Technical Data

MODEL: UT80 – 1/2 HP Submersible Utility Pump

Physical Data:

| | |
|----------------|------------|
| DISCHARGE SIZE | 1-1/4" NPT |
| IMPELLER TYPE | Vortex |
| CABLE LENGTH | 10' |

Liquid Handling:

| | |
|----------------------|----------------------|
| SOLIDS SIZE | 1/8" |
| MAXIMUM LIQUID TEMP. | 104°F – Intermittent |
| ACCEPTABLE PH RANGE | 6-8PH |

Temperature:

| | |
|-----------------|-------|
| MAXIMUM STATOR | 120°C |
| OIL FLASH POINT | 145°C |

Technical Data:

| | |
|-----------------|------------|
| POWER CORD TYPE | SJTW 18/3C |
|-----------------|------------|

| | |
|---------------|-----------------|
| MOTOR HOUSING | Thermal plastic |
| CASING | NA |
| IMPELLER | Thermal plastic |
| MOTOR SHAFT | SS430 |
| HARDWARE | SUS |
| "O" RINGS | NBR |

| | |
|------------------|----------|
| MECHANICAL SEALS | Standard |
| UPPER BEARING | 608-2RS |
| LOWER BEARING | 6200 |



P U M P

Honest, Professional, Dependable

1899 Cottage Street, Ashland, Ohio 44805
Telephone: 855 281-6830 · Fax: 877 326-1994 · ashlandpump.com